

# Indicator/

Digital Indicators  
with alarms

## REX-AD410

Moni+Alarm

AO Moni+Alarm

W96 x H48 D100



### Main Features

- Large LED display
- Universal inputs
- Peak and bottom hold
- Digital outputs (max.6)
- Digital communication
- Analog output
- Digital input

Input	T/C, RTD DC voltage/current
Sampling	0.5 sec
Accuracy	±(0.3% of span + 1 digit)
Digital outputs	Relay (max. 6)
Analog output	DC voltage/current
Digital communication	RS-485/422A (RKC/ANSI)

Digital Indicators  
with alarms

## AE500

Moni+Alarm

W96 x H48 D100



white

### Main Features

- Large LED display
- Digital outputs (max.4)
- Digital communication
- Analog output

Input	T/C, RTD DC voltage/current
Sampling	0.5 sec
Accuracy	±(0.3% of display value + 1digit)
Digital outputs	Relay (max. 4)
Analog output	DC current
Digital communication	RS-485 (RKC/ANSI)

Digital Indicators


## REX-DP410 REX-DP110

W96 x H48 D100



Temp.Moni

W48 x H48 D100



Temp.Moni

AC410/110 with  
alarm functions



REX-DP410



REX-DP110

Input	T/C, RTD DC voltage/current
Sampling	0.5 sec
Accuracy	±(0.3% of span + 1 digit)

Input Selector Unit

## SP400

Black and white  
base available

W48 x H96 D100

## SP500

W96 x H48 D100



black SP500

SP400

white